

PRODUCT NAME:
SHALIMAR INTERIOR EXTERIOR ACRYLIC WALL PRIMER



INTERIOR EXTERIOR ACRYLIC WALL PRIMER

Shalimar Interior Exterior Acrylic Wall Primer is a water dilutable two in one interior exterior primer based on specially designed acrylic emulsion can be used in both interior and exterior surfaces. It gives better coverage, adhesion along with anchoring to top coat.

PRODUCT BENEFITS



EXCELLENT
WHITENESS



REDUCED
PATCHINESS



GOOD
COVERAGE



EXCELLENT
ADHESION



QUICK
DRYING

PRODUCT FEATURES

DRYING TIME
AT 30°C



SURFACE DRY
30 MIN.

HARD DRY
4 HRS.

AVAILABLE
PACK SIZES



1 Ltr



4 Ltr



10 Ltr



20 Ltr

SHELF
LIFE



3 Years
FROM THE DATE OF MANUFACTURING

COLORS
AVAILABLE



WHITE
COLOR

FINISH



SOFT MATT



SOFT SHEEN



HIGH SHEEN



SMOOTH

COVERAGE



14-18
SQ.M/LITRE/COAT*
INTERIOR SMOOTH
SURFACE

10-12
SQ.M/LITRE/COAT*
EXTERIOR ROUGH
SURFACE

APPLICATION DETAILS

Surface Preparation

- New surface to be cured 28 days before painting and free from all waterproofing issues.
- Prepare the surface by using suitable sand/emery paper or scrapping tools to remove dirt, dust, grease, loose flaking paint, laitance, algae, fungi etc. and wipe it clean.

a) Primer

- Apply coat of Shalimar Interior Exterior Acrylic Wall primer by thinning with potable water 1:1 ratio. Allow it to dry for 3-4 hrs.
- Spot prime before and after filling nail holes / cracks.

b) Putty (if required)

- Level the surface with Shalimar Magic Acrylic Wall Putty or Shalimar Shakti
- Wall Guard putty and allow it to dry for 4-6 hrs.
- Sand surface with 180/320 emery paper and wipe it clean.
- Apply an additional coat depending upon the surface conditions and smoothen the surface.

c) Primer

- Apply coat of Shalimar Interior Exterior Wall Primer by thinning with potable water 1:1 ratio. Allow it to dry for 3-4 hrs.

d) Top Coat

- Apply 2 coats of Shalimar Interior Emulsion or Shalimar Exterior Emulsion as per the recommended dilution at an interval of 4-6 hrs. Additional coat of top coat may be required for dark shades.

e) Application Surfaces

- All kind of well-prepared exterior plasters, concrete and masonry surfaces.

PRECAUTIONS



- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application.
- Do not apply when humidity is greater than 90%. It may cause prolonged drying time of paint and moisture condensation on the walls.
- Do not over-thin or over-extend the brush.
- Tint using Shalimar Paints machine colorants only.
- Stir well and strain before use.
- Tinted shades need thorough shaking immediately after colourants addition as well as before use.
- For best performance, ensure that the surface is dry. On moisture meter, the reading should be below 16%. In case it is above that, find out the source of water and address it before painting.
- For better washability ensure the paint surface is cured for 2 weeks under normal atmospheric conditions (30°C ; 50 - 60%RH].
- Application of Acrylic Wall Putty and adherence to the painting system is mandatory for best results.

SAFETY FEATURES



- Kindly refer to the MSDS for detailed information on safety measures while handling the paint, which is available on request.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- Keep out of reach of children and away from eatables.
- May be harmful, if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapour or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Left-Over Material Disposal: Left-over material/drums should not be disposed in soil/drains. Consumers should consult a local recycling agency for proper disposal of paint/drum.
- In the event of spills, contain spillage using sand or earth.
- No added Lead, Mercury or Chromium compounds.

For Feedback/Complaints write at feedback@shalimarpaints.com

Registered Corporate Address Shalimar Paints, Stainless Centre, 4th Floor, Plot No. 50, Sector - 32, Gurugram, 122001, Haryana
Tel.: 0124-4616600, Toll Free : 1800-103-6509

DISCLAIMER

[*Spreading Capacity may vary depending upon the surface condition, porosity of the surface and method of application]

This PDS is by no means a comprehensive data. The company will not be liable for losses or damages howsoever caused including liability for negligence, which may be suffered by the user of the data contained therein. It is the user's responsibility to conduct all necessary tests to confirm the suitability of any product or system for their intended use. No guarantee of result is extended since conditions of use are beyond our control.