

PRODUCT NAME:  
SILK ECO INTERIOR EMULSION



# SILK ECO INTERIOR EMULSION

Shalimar Silk Eco Interior Emulsion is a water-based acrylic emulsion offering smooth and luxurious matt finish with higher opacity and excellent coverage. It provides value for money to a Distemper customer.

## PRODUCT BENEFITS



VALUE FOR  
MONEY



SMOOTH MATT  
FINISH



COVERAGE - TWICE  
THAT OF ORDINARY  
DITEMPER



LOW VOC

## PRODUCT FEATURES

### WASHABILITY



### AVAILABLE PACK SIZES



### SHELF LIFE



### COLORS AVAILABLE



### FINISH



### COVERAGE



## APPLICATION DETAILS

### Surface Preparation

- New surface to be cured 28 days before painting and free from all waterproofing issues.
- Prepare the surface by using suitable sand/emery paper or scrapping tools to remove dirt, dust, grease, loose flaking paint, laitance, algae, fungi etc. and wipe it clean.
- a) **Primer**
  - Apply coat of Shalimar Water Thinnable Cement Primer/Shalimar Interior Exterior Acrylic wall Primer as per recommendation. Allow it to dry for 3-4 hrs.
  - Spot prime before and after filling nail holes / cracks.
- b) **Putty (if required)**
  - Level the surface with Shalimar Magic Acrylic Wall Putty or Shalimar Shakti Wall Guard putty and allow it to dry for 4-6 hrs.
  - Sand surface with 180/320 emery paper and wipe it clean.
  - Apply an additional coat depending upon the surface conditions and smoothen the surface.
- c) **Primer**
  - Apply coat of Shalimar Water Thinnable Cement Primer/Shalimar Interior Exterior Acrylic wall Primer as per recommendation. Allow it to dry for 3-4 hrs.
- d) **Top Coat**
  - Thin Silk Eco Interior Emulsion with potable water, 50% to 75% by volume.
  - For Deep, Accent base & dark shade thin with potable water 20-30% by volume.
  - Apply 2 coats of Silk Eco Interior Emulsion with an interval of 4-6hrs.
  - Application can be done by brush, roller or spray.
  - For dark shades require additional coats for better hiding and appearance.
- e) **Application Surfaces**
  - All kind of well-prepared interior plasters, concrete and masonry surfaces.

## PRECAUTIONS



- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application.
- Do not apply when humidity is greater than 90%. It may cause prolonged drying time of paint and moisture condensation on the walls.
- Do not over-thin or over-extend the brush.
- Tint using Shalimar Paints machine colorants only.
- Stir well and strain before use.
- Tinted paints need thorough shaking immediately after tinter addition as well as before use.
- For best performance, ensure that the surface is dry. On moisture meter, the reading should be below 16%. In case it is above that, find out the source of water and address it before painting.
- For better washability ensure the paint surface is cured for 2 weeks under normal atmospheric conditions (30°C ; 50 - 60%RH].
- Application of Acrylic Wall Putty and adherence to the painting system is mandatory for best results.

## SAFETY FEATURES



- As a general safety measure, inhalation of paint mist and contact of liquid paint with skin & eyes should be avoided.
- Forced ventilation should be provided when applying paint in confined spaces or stagnant air.
- Even when ventilation is provided, respiratory, skin and eye protection are always recommended when spraying paint.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- Keep out of reach of children and away from eatables.
- May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application .In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapors or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Left-Over Paint Disposal: Left-overpaint/drums should not be disposed in soil/drains. Consumers should consult a local recycling agency for proper disposal of paint/drums.
- In the event of spills, contain spillage using sand or earth.
- No added Lead, Mercury or Chromium compounds.

For Feedback/Complaints write at [feedback@shalimarpaints.com](mailto:feedback@shalimarpaints.com)

**Registered Corporate Address** Shalimar Paints, Stainless Centre, 4th Floor, Plot No. 50, Sector - 32, Gurugram, 122001, Haryana  
Tel.:0124-4616600, Toll Free : 1800-103-6509

### DISCLAIMER

(\*Spreading Capacity may vary depending upon the surface condition, porosity of the surface and method of application)

This PDS is by no means a comprehensive data. The company will not be liable for losses or damages howsoever caused including liability for negligence, which may be suffered by the user of the data contained therein. It is the user's responsibility to conduct all necessary tests to confirm the suitability of any product or system for their intended use. No guarantee of result is extended since conditions of use are beyond our control.