



WATERPROOF PUTTY



Shalimar Waterproof Wall Putty is a white cement based, premium quality putty. It can be used on interior as well as exterior concrete/mortar surfaces to provide added water resistance with a smooth aesthetic finish as well as an extended life of top coat.

PRODUCT BENEFITS



WATER RESISTANT



GOOD COMPRESSIVE STRENGTH & FLEXURAL STRENGTH



BEST IN CLASS WHITENESS



EXCELLENT ADHESION



SMOOTH & UNIFORM FINISH TO ROUGH PLASTERS

PRODUCT FEATURES

Colour	White <small>*Please note, SmartCare Waterproof Wall Putty is an undercoat</small>
Shelf Life	1 Year
Coverage	2 COATS 1 - 1.5 sq.m/kg <small>for upto 1.5 mm thickness in 2 coats on rough masonry surface</small>
Recommended usage	It can be used on all types of exterior cement plasters/interior walls, asbestos sheets, concrete etc.
Drying time to recoat	4-6 hrs

AVAILABLE PACK SIZES



20kg



30kg

APPLICATION PROCESS

- Ensure that the surface is free from dirt, loose particles etc.
- Mix waterproof putty with portable water slowly.
- Ensure that proper(homogenous) paste is formed.
- This homogenous paste is ready for application.
- This paste should not be kept more than 3 hours or else it will become hard.
- Please make fresh paste every time as per requirement.
- Pre wetting surface with water is recommended before application.
- Level the surface with homogeneous paste and allow it to dry for 4-6 hours.
- Apply additional coat of putty as per surface condition and surface smoothness requirement.

PRECAUTIONS



- Do not apply when the ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application.
- Ensure homogeneity of the paste

SAFETY FEATURES



- Store it in a cool, dry place
- Keep out of reach of children and away from eatables.
- May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- In the event of spills, contain spillage using sand or earth.
- No added Lead, Mercury or Chromium compounds.

For Feedback/Complaints write at feedback@shalimarpaints.com

Registered Corporate Address Shalimar Paints, Stainless Centre, 4th Floor, Plot No. 50, Sector - 32, Gurugram, 122001, Haryana
Tel.: 0124-4616600, Toll Free : 1800-103-6509

DISCLAIMER

(*Spreading Capacity may vary depending upon the surface condition, porosity of the surface and method of application)

This PDS is by no means a comprehensive data. The company will not be liable for losses or damages howsoever caused including liability for negligence, which may be suffered by the user of the data contained therein. It is the user's responsibility to conduct all necessary tests to confirm the suitability of any product or system for their intended use. No guarantee of result is extended since conditions of use are beyond our control.